

## **SECTION 3306 – PROTECTION OF PEDESTRIANS**

*3306.10 Add a section as follows:*

**3306.10 Chutes.** Chutes for the removal of materials and debris shall be provided in all parts of demolition operations that are more than 20 feet (6.096 m) above the point where the removal of material is effected. Such chutes shall be completely enclosed. They shall not extend in an unbroken line for more than 25 feet (7.62 m) vertically but shall be equipped at intervals of 25 feet (7.62 m) or less with substantial stops or offsets to prevent descending material from attaining dangerous speeds.

The bottom of each chute shall be equipped with a gate or stop with a suitable means for closing or regulating the flow of material.

Chutes, floors, stairways and other places affected shall be watered sufficiently to keep down the dust.

*3306.11 Add a section as follows*

**3306.11 Falling debris.** Wood or other construction materials shall not be allowed to fall in large pieces onto an upper floor. Bulky materials, such as beams and columns, shall be lowered and not allowed to fall.

*3306.12 Add a section as follows*

**3306.12 Structure stability.** In buildings of wood frame construction, the supporting structure shall not be removed until the parts of the structure being supported have been removed.

In buildings with basements, the first floor construction shall not be removed until the basement walls are braced to prevent overturning, or an analysis acceptable to the Building Official is submitted which shows the walls to be stable without bracing.

## **SECTION 3307 – PROTECTION OF ADJOINING PROPERTY**

*3307.1 Insert a note at the end of this section as follows:*

**3307.1 Protection required.** Adjoining public and private property shall be protected from damage during construction, remodeling and demolition work. Protection must be provided for footings, foundations, party walls, chimneys, skylights, and roofs. Provisions shall be made to control water runoff and erosion during construction or demolition activities. The person making or causing an excavation to be made shall provide written notice to the owners of adjoining buildings advising them that the excavation is to be made and that the adjoining buildings should be protected. Said notification shall be delivered not less than 10 days prior to the scheduled starting date of the excavation.

**Note:** Other requirements for protection of adjacent property of adjacent and depth to which protection is requested are defined by California Civil Code Section 832, and is reprinted herein for convenience.

**Section 832.** Each coterminous owner is entitled to the lateral and subjacent support which his land receives from the adjoining land, subject to the right of the owner of the adjoining land to make proper and usual excavations on the same for purposes of construction or improvement, under the following conditions:

1. Any owner of land or his lessee intending to make or to permit an excavation shall give reasonable notice to the owner or owners of adjoining lands and of buildings or other structures, stating the depth to which such excavation is intended to be made, and when the excavating will begin.

2. In making any excavation, ordinary care and skill shall be used, and reasonable precautions taken to sustain the adjoining land as such, without regard to any building or other structure which may be thereon, and there shall be no liability for damage done to any such building or other structure by reason of the excavation, except as otherwise provided or allowed by law.