

PROJECT:

**BLOCK 32
MISSION BAY**
San Francisco, California

Log of Boring B32-2

PAGE 3 OF 3

DEPTH (feet)	SAMPLES			LITHOLOGY	MATERIAL DESCRIPTION	LABORATORY TEST DATA					
	Sampler Type	Sample	SPT N-Value ¹			Type of Strength Test	Confining Pressure Lbs/Sq Ft	Shear Strength Lbs/Sq Ft	Fines %	Natural Moisture Content, %	Dry Density Lbs/Cu Ft
61	SPT		31	SC	CLAYEY SAND (SC) (continued)	COLMA					
62											
63					SERPENTINITE intensely fractured, friable, moderately weathered, low harness	BEDROCK					
64	SPT		50/ 3"								
65											
66											
67											
68											
69	SPT		50/ 4.5"								
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											
84											
85											
86											
87											
88											
89											
90											

Boring terminated at a depth of 69.4 feet.
Boring backfilled with cement grout.
Groundwater encountered at 8 feet at 2:45 pm on
4/27/07.

¹ S&H blow counts converted to SPT N-values using a
factor of 0.6.
² Elevation based on San Francisco City Datum plus 100
feet.

Treadwell & Rollo

Project No.:

4086.17

Figure:

A-2c