FRACTURING

Intensity

Very little fractured Occasionally fractured Size of Pieces in Feet Greater than 4.0 1.0 to 4.0

Moderately fractured 0.5 to 1.0 Closely fractured 0.1 to 0.5 Intensely fractured 0.05 to 0.1

1. Soft - reserved for plastic material alone.

Less than 0.05

П **HARDNESS**

Crushed

- 2. Low hardness can be gouged deeply or carved easily with a knife blade.
- 3. Moderately hard can be readily scratched by a knife blade; scratch leaves a heavy trace of dust and is readily
- visible after the powder has been blown away. 4. Hard - can be scratched with difficulty; scratch produced a little powder and is often faintly visible.
- 5. Very hard cannot be scratched with knife blade; leaves a metallic streak.

STRENGTH III

- 1. Plastic or very low strength.
- 2. Friable crumbles easily by rubbing with fingers. 3. Weak - an unfractured specimen of such material will crumble under light hammer blows.
- 4. Moderately strong specimen will withstand a few heavy hammer blows before breaking.
- 5. Strong specimen will withstand a few heavy ringing hammer blows and will yield with difficulty only dust and
- small flying fragments. 6. Very strong - specimen will resist heavy ringing hammer blows and will yield with difficulty only dust and small flying fragments.
- IV WEATHERING The physical and chemical disintegration and decomposition of rocks and minerals by natural processes such as oxidation, reduction, hydration, solution, carbonation, and freezing and thawing.
- D. Deep moderate to complete mineral decomposition; extensive disintegration; deep and thorough discoloration; many fractures, all extensively coated or filled with oxides, carbonates and/or clay or silt.
 - M. Moderate slight change or partial decomposition of minerals; little disintegration; cementation little to unaffected. Moderate to occasionally intense discoloration. Moderately coated fractures.
 - L. Little no megascopic decomposition of minerals; little of no effect on normal cementation. Slight and intermittent, or localized discoloration. Few stains on fracture surfaces. F. Fresh - unaffected by weathering agents. No disintegration of discoloration. Fractures usually less numerous than ioints.

ADDITIONAL COMMENTS:

CONSOLIDATION OF SEDIMENTARY ROCKS: usually determined from unweathered samples. Largely dependent on cementation.

U = unconsolidated P = poorly consolidated M = moderately consolidated W = well consolidated

VI BEDDING OF SEDIMENTARY ROCKS

Blocky

Slabby

Flaggy

Shaly or platy Papery

Splitting Property Thickness Massive

Greater than 4.0 ft.

2.0 to 4.0 ft.

0.2 to 2.0 ft.

0.01 to 0.05 ft. less than 0.01

thick bedded thin bedded 0.05 to 0.2 ft. very thin-bedded

laminated thinly laminated

Stratification

very thick-bedded

MISSION BAY San Francisco, California

BLOCKS 29-32

A LANGAN COMPANY

PHYSICAL PROPERTIES CRITERIA FOR ROCK DESCRIPTIONS

Date 11/15/11 | Project No. 750603902 | Figure A-26